

Name	
Store #	
Date	
Serial #	



**ASSEMBLY CHECKLIST**  
**ZERO TURN MOWER**  
**MODEL NUMBER ZT4200L/ZT4200L-FC**



CHECK



**A. UNPACKING**

1	Remove the black plastic wrap. Cut all nylon straps. <b>DO NOT USE KNIFE!</b>
2	Hand the Battery and Charger boxes to store manager. <b>DO NOT OPEN THESE BOXES!</b>
3	Open the Accessory box and take wrenches and bolts required for assembly.
4	Unscrew 18 nut/bolt assemblies using included open-ended wrenches or an optional Impact wrench with 1/2 in (13 mm) socket. Disassemble the metal frame and remove the metal loops around rear wheels.
5	Remove the Seat and the Steering Levers
6	Disengage the Parking Brake Pedal and remove the two Wheel Chocs that block the front wheels.
7	Roll the mower off of the bottom frame using a ramp. Push the mower forward. <b>DO NOT PUSH THE MOWER BACKWARD!</b>

**B. SEAT INSTALLATION**

8	Securely connect the Cable Plug to the Socket on the bottom of the Seat.
9	Install and securely fasten the Seat to the Suspension base using 4 socket-head screws (2 in front and 2 in the back) and the Allen key. <b>Note:</b> there are 2 spare screws.
10	Snap the cable into the plastic hook below the Seat front.

**C. ATTACHING THE STEERING LEVERS**

11	Attach the <b>left</b> Steering Lever to the <b>left</b> Mounting pole using 2 hex bolts. Use included open-end wrench.
12	Attach the <b>right</b> Steering Lever to the <b>right</b> Mounting pole using 2 hex bolts. Use included open-ended wrench. Make sure that both Steering Levers are installed at the same height. Prior to tightening the bolts, make sure that the wrenches are aligned horizontally. <b>Note:</b> There are 2 spare bolts.

**D. CHECKING TIRE PRESSURE**

13	Check the tire pressure and adjust the pressure if necessary. Front Wheels – 32 PSI (222.1 kPa); Rear Wheels – 7 PSI (48.3 kPa).
----	--

**E. LEVELING THE MOWER DECK**

14	Raise the mower deck to the highest position using the Mower Deck Height Lever.
15	Position both blades side to side and measure the distance between the ground and the bottom edge of the blade. If the difference in height between the two blades is more than 13/64" (5mm), adjust the deck height.
16	Position both blades front to rear. Measure the distance between the ground and the bottom edge of the blade. The front tip of the blade should be from 5/64 – 25/64" (2mm– 10mm) lower than the rear tip. If necessary, adjust the deck height.

**FINAL STEPS**

17	Inspect the entire product for damaged, missing, or loose parts such as screws, nuts, bolts, caps, etc. Tighten securely all fasteners and caps and do not operate this product until any missing or damaged parts are replaced. Collect 2 open-end wrenches, Allen key, spare screws and bolts (2 each). Place them back into the Accessory Box and hand the box to the store manager. Test drive the unit and its functions.
----	--